

U.S. Application No. 09/539,972  
Attorney Docket No. 99-837  
Customer No. 32,127

**CLAIMS:**

The following listing of claims replaces all prior versions and listings of claims in the application:

1. (Previously Presented) A method for customer centric network management comprising the steps, performed by a processor, of:
  - receiving identification data corresponding to a customer in a network;
  - accessing a generic information model database for one or more customer records corresponding to the customer identification data;
  - receiving selection information identifying a selected one of the one or more customer records, wherein the selected customer record corresponds to the customer;
  - and
  - providing actual circuit path information corresponding to a customer service based on the selected customer record, wherein the actual circuit path information is used to generate a graphical representation of heterogeneous network components supporting a specific service for the customer.

Claim 2 (Canceled).

U.S. Application No. 09/539,972  
Attorney Docket No. 99-837  
Customer No. 32,127

3. (Previously Presented) A method for customer centric network management in a network comprising the steps, performed by a processor, of:
- populating a permanent database with network component information, the permanent database storing the network component information according to a generic information model;
  - receiving customer identification data corresponding to a customer in the network;
  - accessing the permanent database for one or more customer records corresponding to the customer identification data, each customer record having network component information associated with it;
  - receiving selection information identifying a selected one of the one or more customer records, wherein the selected customer record corresponds to the customer; and
  - providing actual circuit path information corresponding to a customer service based on the selected customer record, wherein the actual circuit path information is used to generate a graphical representation of heterogeneous network components supporting a specific service for the customer.

U.S. Application No. 09/539,972  
Attorney Docket No. 99-837  
Customer No. 32,127

4. (Original) The method of claim 3, said populating step further comprising:
  - sending component access information to an element management system, the element management system retrieving network component information from at least one component in the network;
  - receiving the network component information from the element management system; and
  - storing the network component information in the permanent database.
5. (Original) The method of claim 3, further comprising:
  - updating the permanent database based on an automatic event.
6. (Original) The method of claim 3, further comprising:
  - updating the permanent database based on a manual event.
7. (Original) The method of claim 5, said updating step further comprising:
  - collecting new network component information;
  - storing the new network component information in a temporary database;
  - comparing the temporary database with the permanent database; and
  - modifying the permanent database according to comparison rules.

U.S. Application No. 09/539,972  
Attorney Docket No. 99-837  
Customer No. 32,127

8. (Original) The method of claim 6, said updating step further comprising:  
collecting new network component information;  
storing the new network component information in a temporary database;  
comparing the temporary database with the permanent database; and  
modifying the database according to comparison rules.

Claims 9-15 (Canceled).

16. (Previously Presented) A method for customer centric network management comprising the steps, performed by a processor, of:  
receiving identification data corresponding to a customer in a network;  
accessing a generic information model database for one or more customer records corresponding to the customer identification data;  
receiving selection information identifying a selected one of the one or more customer records, wherein the selected customer record corresponds to the customer; and  
providing actual circuit path information corresponding to a customer service based on the selected customer record, wherein the actual circuit path information is used to generate a graphical representation of a customer path.

U.S. Application No. 09/539,972  
Attorney Docket No. 99-837  
Customer No. 32,127

17. (Previously Presented) A method for customer centric network management in a network comprising the steps, performed by a processor, of:

populating a generic information model database with network component information, the database storing the network component information according to a generic information model;

receiving customer identification data corresponding to a customer in the network;

accessing the database for one or more customer records corresponding to the customer identification data, each customer record having network component information associated with it;

receiving selection information identifying a selected one of the one or more customer records, wherein the selected customer record corresponds to the customer; and

providing actual circuit path information corresponding to a customer service based on the selected customer record, wherein the actual circuit path information is used to generate a graphical representation of a customer path.

U.S. Application No. 09/539,972  
Attorney Docket No. 99-837  
Customer No. 32,127

18. (Previously Presented) A network management method comprising the steps, performed by a processor, of:
- using customer identification data capable of identifying a network customer to access one or more stored customer records;
  - selecting at least one of the accessed customer records;
  - determining, as a function of the selected customer record, circuit path information reflecting an actual path in the network used to support a specific service for the customer; and
  - developing a graphical representation of a set of network circuits used to form the actual path.